



Specifications Multipack 4x Ledvance LED Downlight Comfort Opal Aluminium White 30W 3600lm 100D - 930 Warm White | Cutout 200mm - IP44 - Best Colour Rendering

[View Product](#)

General Information

| | |
|--------------------------|---|
| SKU | 257703 |
| EAN | 8719157070737 |
| Brand | Ledvance |
| Manufacturer Name | Multipack 4x DL CMFT D200 P 30W MS 940 OP WT LEDV |
| Any Lamp all-in warranty | 5 Years |
| Average Lifetime (h) | 100000 |

Technical Information

| | |
|-----------------------------|-------------------|
| Emergency Lighting | No Emergency Unit |
| Tiltable | No |
| Technology | LED Integrated |
| Voltage (V) | 220-240 |
| Dimmable | Not Dimmable |
| Colour Code | 930 Warm White |
| Colour temperature (Kelvin) | 3000 Warm White |
| Colour Rendering (Ra) | 90-99 |
| Colour of Light | White |
| Light colour options | Single Color |
| Beam Angle (degree) | 100 |
| Luminous Efficacy (lm/W) | 120 |

| | |
|-----------------------|--------------------------|
| Power factor | >0.90 |
| Unified Glare Rating | < 23 - for general areas |
| Optical Cover | Opal |
| Product Type Category | LED Downlight |

Fixture Information

| | |
|------------------------|------------------------|
| Mounting Method | Recessed |
| Cut out (mm) | 200 |
| IP-rating | IP44 |
| Impact Protection (IK) | IK03 - 0.35 joule |
| Operating Temperature | -20 to +40 |
| Housing | Aluminium |
| Colour of the Fixture | White |
| Fixture Connection | PI [Push-in connector] |

Dimensions

| | |
|---------------|-----|
| Height (mm) | 59 |
| Diameter (mm) | 215 |

Sensor Information

| | |
|----------------|-----------|
| Type of sensor | No Sensor |
|----------------|-----------|

Why Any-lamp?

 Order from the **largest lighting specialist** in Europe  **Customised** quotation

 Up to **7 years warranty**  **Easy** return process